## WHAT IS CLAIMED IS:

1		1	A	
1		1.	An oximeter sensor comprising:	
2	a light emitter for directing light at a patient;			
3	a light detector mounted to receive light from said patient; and			
4	a memory storing coefficients for use in first and second different formulas			
5	for determining oxygen saturation.			
1		2.	The oximeter sensor of claim 1 wherein said coefficients are	
2	dependent on a mean wavelength of said light emitter.			
	•			
1		3.	The oximeter sensor of claim 1 wherein said memory further stores	
2	a value indicating a signal breakpoint between said first and second formulas.			
1		4.	The oximeter sensor of claim 1 wherein at least one of said	
2	different formulas is a nonlinear formula.			
1		5.	The oximeter sensor of claim 1 wherein said different formulas are	
2	linear formulas.			
1		6.	An oximeter sensor comprising:	
2		a light	emitter for directing light at a patient;	
3		_	detector mounted to receive light from said patient; and	
4		_	ory storing coefficients for use in first and second different formulas	
5	for determining oxygen saturation,			
6		said m	emory further storing an indication of a saturation for use in	
7	selecting between said first and second formulas.			
1		7.	The oximeter sensor of claim 6 wherein said coefficients are	
2	dependent on a mean wavelength of said light emitter.			
1		8.	The oximeter sensor of claim 6 wherein said memory further stores	
2			gnal breakpoint between said first and second formulas.	
_	will introduce	0 " 51	2	
1		9.	The oximeter sensor of claim 6 wherein at least one of said	
2	different formulas is a nonlinear formula.			

1	10. The oximeter sensor of claim 6 wherein said different formulas are		
2	linear formulas.		
1	11. An oximeter sensor comprising:		
2	a light emitter for directing light at a patient;		
3	a light detector mounted to receive light from said patient; and a memory		
4	storing a plurality of alternate values of oxygen saturation or ratio-of-ratio values used to		
5	determine oxygen saturation, said plurality of values corresponding to a mean wavelength		
6	of said light emitter.		
1	12. The sensor of claim 11 wherein said values are usable for		
2	interpolation.		